


# 50179 UTILITY FLUSH H-240

**DESCRIPTION** Ideal for flush cutting protruding PVC, Polyethylene pipes and plastic, Lead tubes.



## SPECIFICATION

BLADE THICKNESS	KERF	PITCH (TPI)	BLADE LENGTH	
0.6 mm	0.6 mm	1.5 mm (17 TPI)	225 mm	

## FEATURES

1. Allows access to more confined spaces than a traditional Western hacksaw.
2. Impulse Hardened high quality sharp teeth are designed for long-lasting great performance.
3. Thin blade and perfectly ground teeth are ideal for fine detail cutting leaving an incredibly smooth cut surface.
4. Electroless nickel-phosphorus plated saw blade for rust prevention.
5. Flexible saw blade with no set on the teeth is ideal for flush cutting protruding pipes, dowels, wedges etc. without marring cutting surface.
6. Easy blade replacement with one simple tap.





## RECOMMENDED HANDLE (GROUP -E)

CODE	LENGTH
50323	126 mm



**PISTOL H-126 RED**



## ATTACHABLE HANDLE (GROUP -E)

CODE	LENGTH	
50322	126 mm	<b>PISTOL H-126 BLUE</b> 
50321	126 mm	<b>PISTOL H-126 YELLOW</b> 
50302	240 mm	<b>STRAIGHT H-240 WOOD LH</b> 
50303	240 mm	<b>STRAIGHT H-240 WOOD SH</b> 

## REPLACEMENT OF SAW BLADE

<b>DETACHING BLADE</b>		<ol style="list-style-type: none"> <li>1. Wrap the handle in a rag or towel for safety.</li> <li>2. Tap the handle end with the saw teeth facing upward to loosen the blade.</li> <li>3. Pull the blade out of the spine.</li> </ol>
<b>ATTACHING BLADE</b>		<ol style="list-style-type: none"> <li>1. Wrap the handle in a rag or towel for safety.</li> <li>2. Insert the blade into the spine, and hook onto the pivot.</li> <li>3. Squeeze the blade into the gap of the spine as a temporary lock.</li> <li>4. Tap the handle end gently with the saw teeth facing downward to fix the blade firmly.</li> </ol>
<b>CAUTION</b>	Since the saw teeth are very sharp, we recommend that you wear gloves or wrap the blade with something (a cloth or towel or its cardboard sleeve) when replacing the blade.	