

H-250 hardwood

Catalogue number 50163 (blade) fits handles 50306/08/09/10/11. Was part number 15204.

Specially designed robust and sharp teeth are ideal for cutting Solid wood, conventional sawn wood, plywood, laminated wood.

Applicable cutting materials : Ipe, Bubinga, Ebony, Senna.siamea, Bongossi, Zelokova, chestnut, Japanese cedar, Oak, Turnip etc.





SPECIFICATION

PITCH	BLADE LENGTH	BLADE THICKNESS	KERF
1.75mm (14 TPI)	250mm	0.50mm	0.68mm

FEATURES

- Induction impulse hardened teeth designed for cutting dense timber and long life.
- Sturdy and precisely ground universal teeth suitable for rip/cross/slant cutting leaving an incredibly clean cut surface.
- Interchangeable blade is much more economical than built-in style.
- Nickel-plated saw blade for rust prevention.
- Easy blade replacement with one simple tap.

REPLACEMENT OF SAW BLADE

Detaching blade	Attaching blade
 <p>Tap the back of the handle to detach the blade.</p>	 <p>Hook the blade into the spine and tap the handle to fix the blade.</p>

CAUTION:

Since the saw teeth are very sharp, we recommend that you wear gloves or wrap the blade with something (a cloth or towel or its cardboard sleeve) when replacing the blade.