

## P-210 tuck-in coarse

Blade part number 50122, handle 50337. Previously 18201.

Specially designed Universal teeth (rip/cross/slant) for incredible cutting performance on sawn wood, plywood, laminated wood, composite panel, veneer, and pruning trees etc. An ideal general purpose saw for your toolbox.



### SPECIFICATION

PITCH	BLADE LENGTH	BLADE THICKNESS	KERF
3.00mm (8 TPI)	210mm	0.90mm	1.18mm

### FEATURES

- Screw-locking style is simple and safe.
- Quality aluminium handle with rubberized grip, folds for safe storage.
- High quality sharp teeth (impulse hardened) are designed for long-lasting great performance.
- Interchangeable blade style saves you money.
- Nickel-plated saw blade for rust prevention.
- Specially designed universal teeth for rip/cross/slant cutting.
- **The cutting angle can be adjusted to 2 positions.**

### REPLACEMENT OF SAW BLADE

Detaching blade	Attaching blade
<ul style="list-style-type: none"> <li>● Unfasten the bolt.</li> <li>● Pull the nut out.</li> <li>● Remove the blade.</li> </ul>	<ul style="list-style-type: none"> <li>● Insert the blade into the handle.</li> <li>● Put the bolt into the hole and connect to the nut.</li> <li>● Fasten the bolt <b>tightly</b>.</li> </ul>

**CAUTION:** Since the saw teeth are very sharp, we recommend that you wear gloves or wrap the blade with something (a cloth or towel or its cardboard sleeve) when replacing the blade.

CAUTION: Be careful not to lose the spring washer when changing the blade.

